

BBE SP90 – High Power LED Streetlight



Features / Benefits

- ▼ **Low Power Consumption** - 28W
- ▼ **High Brightness** - Up to 2,100 Lumens, 8 TIMES than the incandescent lamps
- ▼ **Long Life** - Up to 50,000 Hours, adopted the PWM constant current power, protect the LEDs efficiently
- ▼ **Robust Design** - shock and vibration resistant
- ▼ **Light Beam** - Low heat generated/No UV, adopted the integrative lamp cup & radiator, scatter heat quickly
- ▼ **Easy Installation** - Fits standard Edison 40 socket and replace the high pressure sodium lamp directly
- ▼ **Save Money** - Reduces labor and maintenance costs
- ▼ **High Efficiency** – Power Factor>90%, THD<9

Specifications:

1	Revolutionary Photometric Design - The world's first dedicated optical system (rectangular beam focusing lens). Reasonable control of the light distribution, spot rectangular beam pattern, and ensure an ideal uniformity of brightness on the road surface;
2	Unique Integrated Lens and Lampshade Design - Array Lens play a protective and spot light role, avoid wasteful duplication of light and reduce the loss of light, also reduce the weight of the product and enable simplified structure;
3	Creative Design of the Radiator and Lampholder Integration - Fully protect LED life and heat dissipation requirements, satisfied with the structure and design of LED Lights fundamentally, with the most distinctive features of LED Lights(see attached picture);
4	Standard E40, 360-degree Rotation Lamp Holder - It can still rotate after full tightening the lamp holder arbitrarily, adjust to ensure the best direction face to the ground;
5	Direct Replacement Light Source Design - Direct replace the existing high-pressure mercury lamp, high pressure sodium lamp, metal halide lamps, no need to change the original lamp shell;
6	Intelligent Current Control - Intelligent current control, whatever any deviant situation, it is able to achieve the precision constant current, ensure the LED can work under the secure current;
7	No Adverse Glare - Eliminate the glare caused by the adverse ordinary lights glare and visual fatigue sight interference, improve driving safety, reduce the incidence of traffic accidents, fully embodies the spirit of "People-oriented Technology" in this product;

BBE SP90 – High Power LED Streetlight

8	No Light Pollution - Light Distribution designed for road lighting, in addition to illuminate the path and will not illuminate the road outside the region. Eliminate the interference signal by the residents of the light into the rest room;
9	No High-voltage, No Dust Adsorption - Eliminate the high-voltage adsorb the dust cause the lampshade become dark, reduce the brightness;
10	No High-temperature, No Aging Yellow Lampshade - Eliminate baking the traditional lampshade which cause aging yellow, shortened life expectancy and decrease the brightness;
11	Wide Working Voltage – The brightness and working life will be reduced if the working voltage change more than 7% for the traditional streetlight, but it will not influence our LED Streetlight at all;
12	Start Without Delay - Reach the normal brightness and do not have to wait when switch on, eliminate a long process of starting of the traditional street lights;
13	No Strobe - Eliminate the visual fatigue which caused by the strobe lights of the traditional street lamps;
14	Impact Resistance, Shock-proof, Without Ultraviolet (UV) and Infrared (IR) Radiation - No filament and glass frames, avoid break of the traditional lamp, without harm to the human body;
15	High Color Index, Nice Coloration - To show the true colors and more brighter;
16	Multiple Color Temperature Options - Color temperature to meet the needs of different occasions, eliminated the low color temperature of the sodium lamp which cause the hypnotic mood and high color temperature of the mercury lamp which cause the depressed mood, observers will feel more comfortable;
17	Tremendous Energy Saving - Used the ultra high power, high brightness LED light source, together with the high power efficiency power supply, which can save energy 50%-80% than the conventional sodium and mercury lamps;
18	Long Life, Up To 50,000 Hours - (Working for 10 hours a day, can be used for more than 13 years), is 5-10 times working life than a traditional sodium or mercury lamp;
19	Green and Environmental Protection - no lead, no mercury, no environmental pollution;
20	Universal Input Voltage - 85-264VAC full voltage range constant, constant-current PWM technology, high efficiency, low-heat, high-precision constant current;
21	No Pollution to Power Network - Power factor ≥ 0.9 , THD $\leq 20\%$, EMI apply with the global universal index, reduce the power loss and transmission lines to avoid contamination of the network of high frequency interference;
22	Work Under Low-voltage and Low-Heat, Safe and Reliable - LED junction temperature can be controlled under an ideal temperature ($T_J < 70^\circ\text{C}$ $T_a = 25^\circ\text{C}$ ambient temperature);
23	Perfect Combination With Solar Energy - Fully exert the advantage of the LED work under low voltage and environmental work, according to the local solar energy resources, electricity and solar power can also be combined. To achieve the best cost performance and high reliability customers;
24	High Luminous Efficiency - LED luminous efficiency of the existing conditions is $\geq 65\text{lm/w}$, with the rapid increase LED brightness, when the luminous efficiency reach 150lm/w , the 400W sodium lamp will be replace by the 100W LED lamp, the luminous efficiency will reach 300lm/w eventually;
25	Have a number of patents for inventions and utility model patents.

BBE SP90 – High Power LED Streetlight

Technical Parameters:

Model Number	SP90
Input Voltage	85-265VAC
Frequency Range	47 ~ 63 Hz
Power Factor(PF)	>0.9
Total Harmonic Distortion (THD)	<20%
Power Efficiency	83 %
Working Voltage	24V DC
LED Consumption	28 W
Power Supply Consumption	7 W
LED Luminous Efficiency	≥80 lm/w
LED Initial Flux	2,500 lm (Tj=25°C)
LED Maintain Flux	2,300 lm (Tj=70°C,Ta=25°C)
Lamp Output Flux	2,100 lm (Tj=70°C,Ta=25°C)
Lamp's Efficiency (%)	>90 %
Illumination (E)	(Height=6 m)≥13 lux (Equal to HPS 33 lux) (Height=8 m) ≥7.5 lux (Equal to HPS 19 lux) (Height=10 m)≥4.5 lux (Equal to HPS 11 lux) (Height=12 m)≥3 lux (Equal to HPS 7.5 lux)
Effective Illuminated Area	20×8 m (Height=6 m) 26×10 m (Height=8 m) 33×13 m (Height=10 m) 40×16 m (Height=12 m)
Color Temperature	Pure White: 5,000 ~ 7,000 K, White White:3,000~4,000K
Color Index(CRI)	Ra>75

BBE SP90 – High Power LED Streetlight

Light Source	BBE Emitter (1 Watt)
Light Distribution Curve / Beam Pattern	Asymmetric (Bat Wing) / Rectangular Beam
The Highest Light Intensity Angle	The Horizontal Axis: 110°, The Vertical Axis: 45°
Beam Angle	The Horizontal Axis: 120°, The Vertical Axis: 60°
Junction Temperature (Tj)	70 ° C ± 1 0% (Ta= 25 ° C)
System Resistance (Rja)	1.4 ° C / W
Working Temperature	- 30 ° C ~ 40 ° C
Working Humidity	10 % ~ 90 % RH
Storage Temperature	10 ° C ~ 85 ° C
Working Life	> 50,000 Hrs
Light Body & Lampshade Material	Aluminum Alloy and PC
Lamp Base	E40
The Dimensions(Units : mm)	Φ 90x275 mm
Net Weight (g)	1 kg
IP Rating	IP 60
Packing	1 pc/White Box, 10 pcs/Carton
Carton Size	690 x 330 x 315 mm
Container Q'ty (pcs)	20'Q: 3,570 pcs 40'Q: 7,350 pcs, 40'HQ: 8,400 pcs
Guaranty	12 Months

BBE SP90 – High Power LED Streetlight

Installation Effects:



Add: Unit 1507, Winning Centre, 29 Tai Yau Street, Sanpokong, Kowloon, Hong Kong

Email: sales@widexhk.com Web: www.widexhk.com Tel: +852-29977378 Fax: +852-29977380